



PERFORMANCE SERIES OPERATING INSTRUCTIONS

- 400-003 Outdoor/Work
- 400-006 Fire (pictured)
- 400-009S Tasker S



Please read the below before using your Performance headlamp as it relays beneficial operating and safety information.

BATTERIES:

- The Performance Series models require four (4) AA batteries each.
- Acceptable battery types (actual run time will depend upon battery quality and charge): Alkaline, Rechargeable or 1.5v Lithium (Li-FeS2).


NOTE: Mixing of used and new, or different batteries is not recommended as this could lead to leakage or explosion.



BATTERY INSTALLATION/REPLACEMENT

For all Performance models:

1. Unscrew the cap of the battery compartment.
2. Install four (4) AA batteries.
 - a. Respect appropriate polarity when installing (the inside of the battery pack indicates proper battery placement; see diagram below).



Battery Orientation in Case

3. Twist cap back on.
 - a. To get cap started, press against the battery pack in order to overcome the Dual-Gasket Seal's friction. You will notice increased friction as you tighten the cap. NOTE: The Dual-Gasket is necessary to create a waterproof seal.
4. Test the light's performance by activating the power/mode switch located at the top left of the light.

BATTERY LIFE

Battery Life is expected as follows:

FULL POWER	6 to 8 hrs
RESERVE POWER	12 to 16 hrs

*Battery life may vary according to Mode Selected, Battery Quality, and prevailing Ambient Conditions.

TASKER S MODEL: P/N 400-009S Only

The Performance Series Tasker S Model includes the following:

- Elastic strap installed
- Silicone strap, for optional use with hard hats, helmets, etc.
- "W" Clip (qty 1): to remote the battery case
- Velcro Helmet Hold Downs (Qty 2): to secure the fit of the Silicone strap onto hard hats

SECURING TO HARD HAT

You will need Qty 2 Velcro Helmet Hold Downs (included):

1. Slide the helmet light onto your hard hat.
2. Insert the Helmet Hold Down through the Helmet slot.
3. Wrap the Helmet Hold down around the Strap and Velcro attach.
4. Repeat on other side.



OPERATIONAL MODES ACCORDING TO P/N:

The following P/N is ON-OFF ONLY: P/N 400-003

The following table is valid for: P/N 400-006 & 400-009S

MODE	DESCRIPTION
1	Full Power
2	Low Power

NOTE: The Performance models above will power off after Mode 2.

STRAPS:

- Silicone Strap ONLY: P/N 400-006
- Elastic Strap ONLY: P/N 400-003
- Elastic & Silicone Straps: P/N 400-009S

Note: The elastic strap is easier to wear when headlamp is used without a helmet/hard hat, or during surgery.

CABLE GUIDE/HELMET HOLD DOWN:



A black cable guide with Velcro (included and installed on strap) intended to be wrapped around both the strap and cable, making the cable less likely to be caught or snagged on any surrounding objects. Qty 2 additional helmet hold downs included with 400-009S only.

REMOVING YOUR BATTERY CASE AND SECURING THE "W" CLIP TO YOUR BATTERY PACK:

Your battery case may be removed off the head strap. You may more easily secure the battery case to a pocket, belt, strap, etc with the use of a "W" Clip (included).

For installation of "W" Clip onto battery case:

1. Compress the "W" Clip by bending the end loops toward each other.
2. Insert one end loop in each of the two clip holes of the battery case.
3. The center bend of the "W" Clip must be on the outside of the curved portion of the battery case as shown.
4. When the "W" Clip is inserted to its maximum depth, the end loops will spring outward and clip in the proper position.




Wearing your headlamp

with the battery case removed:

1. Uncoil the cable.
2. Undo Velcro on side of head strap, slide out battery case and secure head strap back in place.
3. Affix your battery case to pocket, belt, etc.
4. Put on your Headlamp and adjust for comfort.

PRODUCT DURABILITY, ENVIRONMENTAL CONSTRAINTS & CERTIFICATIONS:



CE
CE-EMC
IPX-7

- Meets NFPA 1971-2007 Fire Resistant Requirements: 500°F / 260°C for 30 minutes

NOTE: The elastic strap is not fire resistant.

CARE/CLEANING:

Your FoxFury is a professional tool, but regular maintenance and care of your headlamp will maximize performance. As needed, wash your FoxFury using a soft washcloth, clean water and a mild soap. Be sure that the battery pack is sealed before washing. When done, pat dry with a damp cloth. Be sure to reapply silicone based lubricant onto the o-ring or gasket of the battery pack after cleaning.

DUAL GASKET CARE:

- Use silicone based lubricant grease around the dual gasket seal on the battery pack.
- Every 3-5 battery changes, re-apply silicone grease.
- Every 7-10 battery changes take a thin screwdriver at an angle and lift the gasket. Using a cotton swab or toothpick, apply a layer of silicone grease underneath it. Remove the screwdriver, and then spin the ring in both directions to effectively spread out the silicone grease. Repeat for the second gasket, on the opposite side of the battery pack

CLEANING HEADLAMPS USED FOR SURGERY

To clean the headlamp and cables, you can use:

- *Isopropyl Alcohol (75% concentration or less)*
- *Ethyl Alcohol (75% concentration or less)*

COMMERCIAL CLEANERS: (Approved for most Polycarbonate manufacturers)

- *Joy™ (Proctor & Gamble) - Most Preferred*
- *Palmolive Liquid™ (Colgate Palmolive) - 2nd Preferred*
- *Dawn liquid, Waitrose liquid*
- *Top Job™ (Proctor & Gamble)*

BEWARE: The following are some of the chemicals that will NOT work well with the plastic lens of the headlamp:

- | | |
|---------------------------------|---------------------------------|
| - <i>Acetaldehyde</i> | - <i>Benzyl Alcohol</i> |
| - <i>Chlorobenzene</i> | - <i>Formic Acid (conc.)</i> |
| - <i>Phosphorus Trichloride</i> | - <i>Acetone</i> |
| - <i>Bromobenzene</i> | - <i>Cutting Oils</i> |
| - <i>Gasoline</i> | - <i>Sodium Sulfide</i> |
| - <i>Acrylonitrile</i> | - <i>Butylic Acid</i> |
| - <i>Cyclo Hexanone</i> | - <i>Lacquer Thinner</i> |
| - <i>Sodium Hydroxide</i> | - <i>Ammonia</i> |
| - <i>Carbon Tetrachloride</i> | - <i>Cyclohexene</i> |
| - <i>Methyl Alcohol</i> | - <i>Sodium Nitrate</i> |
| - <i>Benzene</i> | - <i>Caustic Soda Sol. (5%)</i> |
| - <i>Ethyl Ether</i> | - <i>Phenol</i> |

BATTERY PACK MAINTENANCE:

DEALING WITH CORROSION FROM LEAKING BATTERIES

Battery leakage may cause "corrosion" to build in the battery pack contacts, causing light not to function properly.

In case of presence of Corrosion in the battery pack contacts, please follow the suggested steps listed below:

1. Mix 50% vinegar and 50% water.
2. Remove batteries from the battery pack.
3. Pour the combination into the battery pack and let soak for 5 minutes.
4. Remove fluid from inside the battery pack and dry it properly with a paper towel, and a blow drier (make sure no liquid residue is left inside battery pack).
5. Replace your batteries and test the light's function.
6. Repeat as needed.

NOTE: Corrosion from leaking batteries is not covered by warranty.

AVAILABLE ACCESSORIES:

- *Black Silicone Strap, P/N 600-027*
- *3D Fury Glow Silicone Strap, P/N 600-026*
- *Elastic Strap, P/N 60-019*
- *Helmet Hold Down (set of 2), P/N 50-023*
- *Overhead Strap, P/N 600-002*

WARNINGS:

IMPORTANT

FoxFury, LLC is not responsible for the incorrect use of any FoxFury Lighting product.

- Lights are strong enough to cause damage to the human eye.
- Do not stare into LEDs for long periods of time or from a close range (less than 2 feet).
- FoxFury, LLC is not responsible for any injury or damage caused during the use of this product.
- Usage of this product must be supervised by an adult when it is being used by a minor.

- Any FoxFury product should be operated at speeds safe enough to maneuver around surrounding obstacles.
- Do not use under the influence of drugs or alcohol.

LIMITED WARRANTY

FoxFury Limited Warranty & Customer Care Information

FoxFury, LLC ("FoxFury") warrants to the purchaser of this product ("Buyer") that for a period of two years following purchase, this product will be free from defects in material and workmanship and will function in substantial compliance with FoxFury's written specifications for this product as specified in the instruction manual or on FoxFury's website located at www.foxfury.com. Buyer's exclusive remedy shall, in any case, be limited, at FoxFury's election, to: A) repair or replacement of the defective product; or B) refund of the purchase price for this product. THE FOREGOING WARRANTY IS THE ONLY WARRANTY MADE BY FOXFURY WITH RESPECT TO THIS PRODUCT. TO THE EXTENT ALLOWED BY APPLICABLE LAW, THERE ARE NO REPRESENTATIONS OR WARRANTIES OF ANY KIND BY THE FOXFURY, EXPRESS OR IMPLIED, WITH RESPECT TO THE CONDITION OR PERFORMANCE OF THIS PRODUCT, INCLUDING, BUT NOT LIMITED TO, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. **This limited warranty shall not apply if this product is not stored, handled, installed or used in strict accordance with manufacturer's specifications and instruction manuals, or which has been subject to misuse, alteration, negligence or accident.**

1. The damaged part or product must be returned to FoxFury **PRIOR** TO any repair or replacement. Shipping costs are the responsibility of the claimant.
2. You must obtain a return authorization (RMA) number from FoxFury prior to returning products. FoxFury is not responsible for any damage incurred while in transit.
3. Buyer will be required to show proof of purchase – No Exceptions.
4. Any modifications to light, cable or battery pack automatically voids all warranties on this product.

All warranty inquiries should be directed to FoxFury's Customer Service Department to handle all warranty/repair-related inquiries.

TO THE EXTENT ALLOWED BY APPLICABLE LAW: (A) IN NO EVENT, WHETHER DUE TO BREACH OF WARRANTY HEREUNDER OR ANY OTHER CAUSE WHATSOEVER, SHALL FOXFURY BE LIABLE FOR OR OBLIGATED IN ANY MANNER TO PAY CONSEQUENTIAL, INCIDENTAL OR INDIRECT DAMAGES, INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS, COST OF SUBSTITUTE PRODUCTS AND PERSONAL INJURY OR PROPERTY DAMAGE, WHETHER SUCH CLAIM IS BASED ON CONTRACT OR TORT OR ANY OTHER THEORY OF LAW, AND (B) FOXFURY'S ONLY DUTIES IN CONNECTION WITH THE SALE OF THIS PRODUCT SHALL BE TO HONOR THE LIMITED WARRANTY SET FORTH HEREIN. TO THE EXTENT THAT THIS LIMITED WARRANTY IS INCONSISTENT WITH APPLICABLE LAW, THIS STATEMENT SHALL BE DEEMED MODIFIED TO BE CONSISTENT WITH SUCH APPLICABLE LAW.



FoxFury, LLC
Vista, CA 92084 USA
Toll-Free: 844-FOXFURY
Tel: 760.945.4231
Fax: 760.758.6283
Email: Service@foxfury.com
www.FoxFury.com

All FoxFury products are designed in Vista, CA. All FoxFury products are manufactured with the highest quality USA and foreign parts. Products are assembled in either FoxFury's controlled plant in Asia or the USA, under strict quality control.